

NEO-7 series

u-blox 7 GNSS modules

Standard Professional Automotive

POSITIONING

Highlights

- GNSS engine for GPS/QZSS, GLONASS
- Product variants to meet performance and cost requirements
- Combines low power consumption and high sensitivity
- Backward compatible with NEO-6 and NEO-5 families



NEO-7 series:
12.2 x 16.0 x 2.4 mm

Product description

The NEO-7 series of standalone GNSS modules is built on the exceptional performance of the u-blox 7 GNSS (GPS, GLONASS, QZSS and SBAS) engine. The NEO-7 series delivers high sensitivity and minimal acquisition times in the industry proven NEO form factor.

The NEO-7 series provides maximum sensitivity while maintaining low system power. The NEO-7M is optimized for cost sensitive applications, while NEO-7N provides best performance and easier RF integration. The industry proven NEO form factor allows easy migration from previous NEO generations. Sophisticated RF-architecture and interference suppression ensure maximum performance even in GPS-hostile environments.

The NEO-7 combines a high level of robustness and integration capability with flexible connectivity options. Future-

proof the NEO-7N's internal Flash allows simple firmware upgrades for supporting additional GNSS systems. This makes NEO-7 perfectly suited to industrial and automotive applications. The DDC (I²C compliant) interface provides connectivity and enables synergies with u-blox cellular modules. For RF optimization the NEO-7N features an additional front-end LNA for easier antenna integration and a front-end SAW filter for increased jamming immunity.

u-blox 7 modules use GNSS chips qualified according to AEC-Q100 and are manufactured in ISO/TS 16949 certified sites. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

Product selector

Model	Type	Supply	Interfaces	Features	Grade
	GPS / QZSS GLONASS Galileo BeiDou Timing Dead Reckoning Precise Point Positioning Raw Data	1.65 V – 3.6 V 2.7 V – 3.6 V Lowest power (DC/DC)	UART USB SPI DDC (I ² C compliant)	Programmable (Flash) Data logging Additional SAW Additional LNA RTC crystal Internal oscillator Active antenna / LNA supply Active antenna / LNA control Antenna short circuit detection / protection pin Antenna open circuit detection pin Frequency output	Standard Professional Automotive
NEO-7N	• •	• •	• • • •	• • • • • T ○ •	
NEO-7M	• •	• •	• • • •	• C ○	

○ = Optional, not activated per default or requires external components

C = Crystal / T = TCXO

Features

Receiver type	56-channel u-blox 7 engine GPS L1 C/A, GLONASS L1 FDMA, QZSS L1 C/A SBAS: WAAS, EGNOS, MSAS		
Navigation update rate	up to 10 Hz		
Accuracy		GPS	GLONASS
	Position	2.5 m CEP	4 m
Acquisition	SBAS	2.0 m CEP	n.a.
	Cold starts:	29 s	30 s
	Aided starts:	5 s	n.a.
	Reacquisition:	1 s	3 s
Sensitivity	Tracking & Nav:	-162 dBm	-158 dBm
	Cold starts:	-148 dBm	-139 dBm
	Warm starts:	-148 dBm	-145 dBm
Assistance GPS	AssistNow Online AssistNow Offline AssistNow Autonomous OMA SUPL & 3GPP compliant		
Oscillator	TCXO (NEO-7N), crystal (NEO-7M)		
RTC crystal	Built-In		
Noise figure	On-chip LNA (NEO-7M); Extra LNA for lowest noise figure (NEO-7N)		
Anti jamming	Active CW detection and removal; Extra onboard SAW band pass filter (NEO-7N)		
Memory	ROM (NEO-7M) or Flash (NEO-7N)		
Supported antennas	Active and passive		

Electrical data

Supply voltage	1.65 V to 3.6 V (NEO-7M) 2.7 V to 3.6 V (NEO-7N)
Power Consumption	17 mA @ 3 V (Continuous) ¹ 5 mA @ 3 V Power Save mode (1Hz) ¹
Backup Supply	1.4 V to 3.6 V

¹ NEO-7M.

Interfaces

Serial interfaces	1 UART 1 USB V2.0 full speed 12 Mbit/s 1 SPI (optional) 1 DDC (I ² C compliant)
Digital I/O	Configurable timepulse 1 EXTINT input for Wakeup
Timepulse	Configurable 0.25 Hz to 10 MHz
Protocols	NMEA, UBX binary, RTCM

Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.


The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.

Copyright © 2014, u-blox AG

Package

24 pin LCC (Leadless Chip Carrier): 12.2 x 16.0 x 2.4 mm, 1.6 g

Pinout



Environmental data, quality & reliability

Operating temp.	-40° C to 85° C
Storage temp.	-40° C to 85° C
RoHS compliant (lead-free)	
Qualification according to ISO 16750	
Manufactured in ISO/TS 16949 certified production sites	
Uses u-blox 7 chips qualified according to AEC-Q100	

Support products

u-blox 7 Evaluation Kits:

Easy-to-use kits to get familiar with u-blox 7 positioning technology, evaluate functionality, and visualize GNSS performance.

EVK-7N: u-blox 7 GNSS Evaluation Kit, with TCXO, supports NEO-7N

EVK-7C: u-blox 7 GNSS Evaluation Kit, with Crystal, supports NEO-7M

Ordering information

See datasheet

Contact us

For contact information, see www.u-blox.com/contact-us.